

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
26 January 2006 (26.01.2006)

PCT

(10) International Publication Number
WO 2006/009049 A1

(51) International Patent Classification: B60K 6/04

(21) International Application Number:
PCT/JP2005/012970

(22) International Filing Date: 7 July 2005 (07.07.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-208898 15 July 2004 (15.07.2004) JP

(71) Applicant (for all designated States except US): TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KIKUCHI, Yoshiaki [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(74) Agent: ITEC INTERNATIONAL PATENT FIRM; Uchisaiwaicho Dai Bldg., 1-3-3, Uchisaiwai-cho, Chiyoda-ku, Tokyo 1000011 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GI, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HYBRID VEHICLE, CONTROL METHOD OF HYBRID VEHICLE, AND POWER OUTPUT APPRATUS

(57) Abstract: When a drive power demand Pv^* is greater than 0, the control procedure of the invention sets the greater between an engine speed demand $Neng^*$ and a lower engine speed limit $Nemin$ to a target rotation speed Ne^* of an engine (step S160). The engine speed demand $Neng^*$ represents a rotation speed of the engine at a specific drive point that ensures efficient output of an engine power demand Pe^* . The lower engine speed limit $Nemin$ represents a rotation speed of the engine at another specific drive point for a constant-speed drive of a hybrid vehicle at a current vehicle speed V . When the drive power demand Pv^* is equal to 0, the control procedure of the invention cuts fuel supply to the engine and sets the lower engine speed limit $Nemin$ to the target rotation speed Ne^* of the engine (step S190). The engine is accordingly driven at the rotation speed of not lower than the lower engine speed limit $Nemin$ and has a quick response to a demand for output power increase from the engine. This arrangement desirably reduces the loading of a battery and prevents premature deterioration of the battery.

Description

Hybrid Vehicle, Control Method of Hybrid Vehicle, and Power
Output Apparatus

5 Technical Field

The present invention relates to a hybrid vehicle, a control method of the hybrid vehicle, and a power output apparatus.

10 Background Art

One proposed hybrid vehicle has an engine, a planetary gear unit including a carrier and a ring gear respectively linked to a crankshaft of the engine and to a drive shaft, a first motor connected to a sun gear of the planetary gear unit, 15 a second motor connected to the drive shaft, and a battery capable of transmitting electric power to and from the first motor and the second motor (see, for example, Japanese Patent Laid-Open Gazette No. 11-93727). In this proposed hybrid vehicle, the first motor is driven and controlled to regulate 20 the rotation speed of the engine.

Disclosure of the Invention

In the hybrid vehicle equipped with the engine and the driving motor, the general control procedure varies the 25 rotation speed of the engine and intermittently activates and inactivates the engine with a variation in required engine power,